



**- An economic ultra shallow LED luminaire
ideally suited for open plan environments and classrooms.**

- Panel depth of only 9mm enables installation into extremely shallow ceiling void

- Colour Temperatures: 3000k - 4000k
- Wire suspended or surface mounted options available
 - Available with Dimming (/STD/DALI/SDIM/MDIM)
 - Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Surface option available: 600 x 605 x 50mm (with surface mounting frame) (/SM)
- IP65 option available. Please contact the technical department for further details. (/IP65)
- Refer to page 89 for ceiling system options

Product	MIR/FLT Recessed LED Modular		
Lamp	LED		
Lamp Power Luminaire lumens (4000K)	/40W 3600lm	/40W 3600lm	/45W 4100lm
Size Cut-Out	/55 500 x 500mm 494 x 494mm	/66 600 x 600mm 594 x 594mm	/66 600 x 600mm 594 x 594mm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k
Bezel Colour	/WH White		
Diffuser Options	/OP Opal Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: FLATLINE LED, 40W, 4000k, 3600lm LED modular recessed finished white supplied complete with DALI control gear and opal diffuser. Part code: MIR/FLT/40W/3600lm/66/DALI/840/WH/OP			

