

FLATLINE 123



- An economic ultra shallow LED 1200x300mm luminaire ideally suited for open plan environments and classrooms.

- Panel depth of only 9mm enables installation into extremely shallow ceiling void

- A lumen output of 3600-4100lm
- Colour Temperatures: 3000k - 4000k
- Wire suspended or surface mounted options available
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
 - Diffuser: Opal (/OP)
- Dimensions: 1200 x 300 x 9mm
- Depth without driver 9mm
- Depth with driver 42mm
- 1205 x 300 x 50mm (with surface mounting frame) (/SM)
- Refer to page 89 for ceiling system options

Product	MIR/FLT/123 Recessed LED Modular			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/40W 3600lm			/45W 4100lm
Size Cut-Out	/123 1200 x 300mm 1194 x 294mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White			
Diffuser Options	/OP Opal Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: FLATLINE 123 LED, 40W, 4000k, 3600lm LED modular recessed finished white supplied complete with DALI control gear and opal diffuser. Part code: MIR/FLATLINE/40W/3600lm/123/DALI/840/WH/OP				

