











- The FLATLINE UGR19 is the latest in energy efficienct modular lighting providing a low glare lighting solution to the workplace.

Suitable for offices, open area offices, retail outlets, corridors and amenity areas.

- Panel depth of only 10mm enables installation into extremely shallow ceiling void


- A lumen output of 3687lm
- Colour Temperatures: 3000k 4000k
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Exposed Tee ceilings, Spring Tee and other ceiling options available
 - Diffuser Options: UGR (/UGR)
 - Uniform illuminance across the micro prismatic diffuser
 - Finished white

- Dimensions: 600 x 600mm / 1200 x 300mm
 - Depth without driver 10mm
 - Depth with driver 42mm

 $600\,x\,605\,x\,50mm$ / $1205\,x\,300\,x\,50mm$ (with surface mounting

- frame 600) (/SM)
- Refer to page 89 for ceiling system options
- -Wire suspended or surface mounted options available

Product	MIR/FLT-UGR19 Recessed LED Modular			
Lamp	LED			
Lamp Power	/39W 3687lm			
Size Cut-Out	/66 600 x 600mm 594 x 594mm		/123 1200 x 300mm 1194 x 294mm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White			
Diffuser Options	/UGR19 UGR19 Diffuser			
Emergency	/ME3 Three hour main- tained emergency			/ME3-PRO Three hour DALI addressable emergency
To Specify: FLATLINE UGR19 LED, 39W, 4000k, 3687Im LED modular recessed finished white supplied complete with				





To Specify: FLATLINE UGR19 LED, 39W, 4000k, 3687lm LED modular recessed finished white supplied complete wit DALI control gear and UGR19 diffuser. Part code: MIR/FLT-UGR19/39W/3687lm/66/DALI/840/WH/UGR19