



- The HI-LED range is designed for use in open areas where an even uniformity is required.

Suitable for very narrow aisles, general warehousing, garages and areas where a high lumen output and shallow profile body combination is required.

- Tridonic boards providing lumen outputs from 10790-25730lm

- 5 year system warranty for LED

- Colour Temperatures: 3000k - 4000k

- Available with Dimming (/STD/DALI/SDIM)

- Available with Emergency (/ME3/ME3-ST/ME3-PRO)

- Optional daylight sensor available (/DS)

- Surface mounted as standard

- Available with chain suspension/ wire suspension/ drop rods/ trunking mounted (/CS/WS/DR/TM)

- Steel body finished white

- Opal diffuser as standard

- Dimensions: 750/1700mm x 420 x 70mm

Product	MIHILED Low Bay LED		
Lamp	LED		
Lamp Power Luminaire lumens (4000K)	/132W 10790lm	/315W 25730lm	
Size	/07 750mm	/17 1700mm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k
Colour	/WH White		
Diffuser Options	/OP Opal		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: HILED , 132W , 750mm, 10790lm, 4000k, LED surface mounted finished white supplied complete with standard control gear. Part code: MIHILED/07/132W/10790lm/STD/840/WH/OP			

