



ILS6/A6/WH



ILS9/A6/WH



ILS13/A6/WH - ILS18/A6/WH

- The adjustable ILS A6 downlight is a competitive, interchangeable and architectural LED downlight system.

An alternative light engine to a MR16 or GU10 lamp.

The downlight is rotatable through 355 degrees.

- Colour Temperatures: 3000k - 4000k
 - Beam Angles: 22°/ 36°/ 60°
- White as standard, Black and Grey also available
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
 - Materials:
 - Aluminium Housing
 - Polycarbonate reflector with aluminium coating
- Adjustable
- 355° Rotation
- Bezel Dimension Ø110mm
- Cut-out Dimension Ø95mm
- Depth: See images below or page 23

Product	MID/ILS/A6 Recessed ILS A6 Downlight			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/6W 650lm	/9W 905lm	/13W 1100lm	/18W 1800lm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White	/SLV Silver		/GR Grey
Beam Angle Options	/22D 22 Degree	/36D 36 Degree		/60D 60 Degree
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote Three hour maintained self test emergency		/RME3-PRO Remote Three hour DALI addressable emergency
To Specify: MID ILS A6 9W, 60 degree beam angle, 4000k, 905lm LED downlight, with an ILS bezel attachment; A6 in white. Part code: MID/ILS/A6/9W/60D/STD/840/WH				

