



ILS9/G1/BK

- The adjustable ILS G1 MATRIX downlight is a competitive, interchangeable and architectural LED adjustable downlight system.
An alternative light engine to a MR16 or GU10 lamp.

- Colour Temperatures: 3000k - 4000k
 - Beam Angles: 22°/ 36°/ 60°
- White and Black as standard, Grey also available
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
 - Materials:
 - Aluminium Housing
 - Polycarbonate reflector with aluminium coating
- Adjustable
 - Bezel Dimension 110x110mm
 - Cut-out Dimension 100x100mm

Product	MID/ILS/G1/MATRIX Recessed ILS G1 Downlight			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/6W 650lm	/9W 905lm	/13W 1100lm	/18W 1800lm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White	/BK Black	/GR Grey	
Beam Angle Options	/22D 22 Degree	/36D 36 Degree	/60D 60 Degree	
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote Three hour maintained self test emergency	/RME3-PRO Remote Three hour DALI addressable emergency	
To Specify: MID ILS G1 MATRIX 9W, 60 degree beam angle, 4000k, 905lm LED downlight, with an ILS bezel attachment; G1 in white. Part code: MID/ILS/G1/MATRIX/9W/60D/STD/840/WH				

