



ILS/SC/BK

- The ILS surface can is a competitive, interchangeable and architectural LED system.

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°/ 36°/ 60° (/22D/36D/60D)
- White as standard, Black and Unpainted also available
- This fitting can be painted to a RAL colour using the unpainted version
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Dimensions Ø135x207mm
- Materials: Aluminium Housing
Polycarbonate reflector with aluminium coating
- Surface or Suspended
- Suitable for BESA fixing
- Wire Suspension available (/WS)

Product	MID/ILS/SC ILS Surface Can			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/6W 650lm	/9W 905lm	/13W 1100lm	/18W 1800lm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White	/BK Black		/UP Unpainted
Beam Angle Options	/22D 22 Degree	/36D 36 Degree		/60D 60 Degree
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emer- gency		/ME3-PRO Three hour DALI addressable emer- gency
To Specify: MID ILS SC 9W, 60 degree beam angle, 4000k, 905lm LED downlight, with an ILS bezel attachment; SC in black. Part code: MID/ILS/SC/9W/60D/STD/840/BK				

