

MIR700 SEALED RECESSED



Edgware Hospital



St Thomas' Hospital ECP



- An IP65 rated (front) LED luminaire. Ideal for use in environments such as laboratories, hospitals, bathrooms, kitchens, and clean-room environments. Designed to integrate with specific ceiling systems as well as standard lay-in and concealed grid ceilings.

- Range of lumen outputs 3852lm-7886lm
- Dimensions: 600 x 600 x 71mm, 1200 x 300 x 71mm, 1500 x 300 x 71mm, 1200 x 600 x 71mm
- Colour Temperatures: 3000k - 4000k -5000k - Tunable White (TWH)
- Wire suspended or surface mounted options available
- Exposed Tee ceilings, Spring Tee and other ceiling options available
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Additional lumen and wattage options available. Please contact our technical department for details.
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Front and rear IP rated options available. IP65 front rating as standard, IP54 and IP65 rear available (/IP54R/IP65/IP65R)
- Diffuser Options: Polar White / Microprism / Lumieo Panel (/PW/MPO/MPOLP)
- 5 year system warranty
- Refer to page 54-55 for ceiling system options

Product	MIR700 Recessed LED IP65 Modular			
Lamp	LED			
Lamp Power	/35W 3852lm	/35W 3852lm	/45W 4700lm	/70W 7886lm
Size	/66 600 x 600mm	/123 1200 x 300mm	/153 1500 x 300mm	/126 1200 x 600mm
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k	/850 5000k	/TWH Tunable White
Bezel Colour	/WH9010 White - RAL9010		/WH9016 White - RAL9016	
Diffuser Options	/PW Polar White	/MPO Micro Prismatic Optic		/MPOLP MPO with Lumieo
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: MIR700 LED, 35W, 4000k, 3852lm LED modular recessed finished RAL9010 supplied complete with DALI control gear, polar white diffuser and IP65 rated. Part code: MIR700/LED/35W/3852lm/DALI/840/WH9010/PW/IP65				

