



Corridor dimming, PIR and Microwave sensors are available.

- A high quality, GRP vapour resistant luminaire suitable for all indoor and external under cover applications only.

- A range of lumen outputs from 1415-7847lm
- 5 year system warranty for LED
- Colour Temperatures: 3000k - 4000k - 5000k
- Available with Dimming (/STD/DALI/SDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Screw fix mounted as standard. Stainless steel fixing clips are available (/SSSB)
- Rated IP65
- Unique frosted opal polycarbonate diffuser
- Dimensions: Length: 665/1275/1575 Width: 134 Depth: 98.5mm
- Available with wire suspension (/WS)
- Suitable for all indoor and external under cover applications only.
- Microwave sensor, PIR and presence detector for corridor function and circulation areas available (/MW/PIR/CDR)

Product	MIVP Linear LED Vapour Proof Luminaire			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/16.4W 2010lm	/32.8W 4020lm	/40.3W 4945lm	/64.6W 7847lm
Size	/6 665mm	/12 1275mm	/15 1575mm	
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k		/850 5000k
Body Colour	Grey			
Diffuser Options	Opal Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: MIVP LED LED, 32.8W, 1275mm, 4020lm, 4000k, LED surface mounted finished grey supplied complete with standard control gear. Part code: MIVP/LED/32.8W/4020lm/12/STD/840				

