



- A high quality, backlit and efficient LED modular luminaire to suit most commercial ceiling types.

- Part L compliant with an efficacy of 120 L.lm/cW

- 5 year system warranty

- Colour Temperatures: 3000k - 4000k - 5000k - Tunable White (TWH)
 - Available with Dimming (/STD/DALI/SDIM)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Suitable for exposed Tee ceilings, Spring Tee and other ceiling options available
- Additional lumen and wattage options available. Please contact our technical department for details.
- Refer to page 89 for ceiling system options
- Diffuser Options: Polar White / Microprism / Lumieo Panel (/PW/ MPO/MPOLP)
- Diffuser Options: Tpa & Tpb diffuser options available upon request, please contact our technical department for details.
- IP40 as standard.
- Depth with remote gear box 69mm.

Product	MIR/PREMLED Recessed Premier LED Modular			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/33.2W 4004lm	/33.2W 4004lm	/41.6W 5005lm	/64.4W 8008lm
Size (Nominal)	/66 600 x 600mm	/123 1200 x 300mm	/153 1500 x 300mm	/126 1200 x 600mm
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k	/850 5000k	/TWH Tunable White
Colour	/WH White			
Diffuser Options	/PW Polar White	/MPO Micro Prismatic Optic		/MPOLP MPO with Lumieo
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: PREMIER LED, 33.2W, 4000k, 4004lm LED modular recessed finished white supplied complete with DALI control gear and polar white diffuser. Part code: MIR/PREMLED/33.2W/4004lm/66/DALI/840/WH/PW				

