



- An architectural surface and suspended, modular and continuous LED system with an uplight facility.

- A range of lumen outputs from 2860-7930lm
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Painted white RAL9016 as standard, other RAL colours available (/WH)
- Diffuser Options: Polar White/Micro Prismatic (/PW/MPO)
- Colour Temperatures: 3000k - 4000k - 5000k
- Available as surface mounted or wire suspended (/SM/WS)
- Available with Dimming (/STD/DALI/SDIM)
- Available with Uplight (/UDL)
- Dimensions: 1250/1550 x 250 x 76mm

Product	MIS/SPACE2 LED linear luminaire			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/22.2W 2860lm	/32.8W 4063lm	/31W 3961lm	/45.8W 5598lm
Size	/12 1250mm		/15 1550mm	
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k		/850 5000k
Colour	/WH White			
Diffuser Options	/PW Polar White Diffuser		/MPO Micro Prismatic Diffuser	
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: SPACE2 LED, 32.8W, 4063lm, 1250mm, 4000k, LED surface linear finished white supplied complete with DALI control gear, wire suspension and polar white diffuser. Part code: MIS/SPACE2/LED/32.8W/4063lm/12/DALI/840/WH/PW/WS				

