



**- The TRK-2 is a track luminaire with a sleek, minimalistic design, ideally suited for retail, hospitality and leisure environments. Compatible with Global Trac® systems. Visit [www.midlighting.co.uk](http://www.midlighting.co.uk) for full track details.**

- TRK-2 head rotates 355 degrees and pivots through 90 degrees.

The rotating position can be set by the scale marked on the connection to the body.

- Available in a range of lumen outputs from 2300-3400lm
- Colour Temperatures: 3000k - 4000k
- Available with 18D/25D/35D/50D Beam Angles (/18D/25D/35D/50D)
- Available with a CRI90 option (Standard CRI80) (/9CT)
- Available with DALI Dimming (/DALI)
- Dimensions: 205mm x Ø 90mm

Product	MI/TRK-2 LED TRK Spotlight			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/28W 2300lm			/42W 3400lm
Size	205mm x Ø 90mm			
Driver	/STD Non Dimming		/DALI DALI Dimming	
Colour Temperature	/830 3000k	/930 CRI 90 3000k	/840 4000k	/940 CRI 90 4000k
Colour	/WH White		/BK Black	
Beam Angle	/18D 18 Degrees	/25D 25 Degrees	/35D 35 Degrees	/50D 50 Degrees
Emergency	Remote EMLED TRK available. See Page 173 for details.			
To Specify: TRK-2, 42W, 4000k, 3400lm, 35 degree beam angle, LED track spotlight supplied with DALI control gear and finished in black. Part code: MI/TRK-2/42W/3400lm/DALI/840/35D/BK				

