



- The TRK-3 is a track luminaire that is suitable for single or three circuit Global Trac® systems. Ideal for retail, hospitality and leisure applications.

- TRK-3 head rotates and pivots to allow adjustable aiming of luminaire.
- Available in a range of lumen outputs from 1352-4088lm
 - Colour Temperatures: 3000k - 4000k
- Available with 26D/38D/60D Beam Angles (/26D/38D/60D)
 - Available with DALI Dimming (/DALI)
 - Dimensions: 218mm x Ø100mm
- Available with surface mounting adapter (/SMA)
- Compatible with Global Trac® Systems.

Product	MI/TRK-3 LED TRK Spotlight			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/11.5W 1352lm	/18.3W 2117lm	/26.6W 2846lm	/38.2W 4088lm
Size	218mm x Ø100mm			
Driver	/STD Non Dimming		/DALI DALI Dimming	
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White RAL9016		/BK Black RAL9005	
Beam Angle	/26D 26 Degrees	/38D 38 Degrees		/60D 60 Degrees
Emergency	Remote EMLED TRK available. See Page 173 for details.			
To Specify: TRK-3, 18.3W, 4000k, 2117lm, 60 degree beam angle, LED track spotlight supplied with DALI control gear and finished in black. Part code: MI/TRK-3/18.3W/2117lm/DALI/840/BK/60D				

