

APOLLO

G5



A cost effective, high quality LED downlight, the Apollo clear and opal glass has a range of interchangeable reflectors.

The G6 & G7 (830/840) are stock options. Other options available to order.

- A range of lumen outputs from 1400-2000lm
- Colour Temperatures: 3000k - 4000k
- Additional wattages and lumen outputs available, please contact technical for further details
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Diffuser Options: Clear Glass/ Opal (/CL/OP)
- Reflector Options: Silver, White or Black (/SLV/WH/BK)
- Dimensions: (Diameter x Depth)
Ø155 x 111mm
- Cut-out Dimensions: (Diameter) Ø125mm

Product	MID/APL/G5 Recessed APOLLO Downlight				
Light Source	LED				
System Power Luminaire lumens (4000K)	/15W 1500lm	/21W 2000lm	/15W 1400lm	/21W 1800lm	
Diffuser Options	/CL Clear Glass			/OP Opal	
Size Cut-out	Ø 155mm Ø 125mm				
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k			/840 4000k	
Reflector Colour	/WH White	/SLV Silver		/BK Black	
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency	
To Specify: APOLLO G5 LED, 21W, 4000k, 2000lm LED downlight finished white supplied with a clear glass reflector. Part code: MID/APL/G5/21W/2000lm/840/WH/CL Clear reflector 4000k lumen figures only. Opal reflector 4000k lumen figures only.					

Reflector Options

