



Low maintenance, affordable and efficient batten LED luminaire. An energy efficient and high output alternative to T5 fluorescent lamps.

- A range of lumen outputs from 4800-5600lm
- Colour Temperatures: 3000k - 4000k - 6500k
- Colours: White as standard. Painting to RAL colours available.
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Diffuser: High transmission opal (/OP)
- Nominal Dimensions: (length x Width x Height) 1175 / 1475 x 62 x 70 mm

Product	MIB Surface LED linear							
Light Source	LED							
System Power Luminaire lumens (4000K)	/22W 2978lm	/28W 3763lm	/34W 4275lm	/40W 4947lm	/35W 5299lm	/40W 5680lm	/50W 6772lm	/57W 7611lm
Size	/12 1175mm				/15 1475mm			
Driver	/STD Non Dimming		/DALI DALI Dimming		/SDIM Switch Dimming		/WI Wireless Control	
Colour Temperature	/830 3000k		/840 4000k				/850 6500k	
Colour	/WH White							
Diffuser Options	/OP High transmission opal							
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency		/ME3-PRO Three hour DALI addressable emergency			/ME3-WI Three hour Wireless addressable emer- gency	
To Specify: BATTEN LED, 50W, 4000k, 6772lm LED surface linear finished white RAL9016 supplied complete with DALI control gear and opal diffuser. Part code: MIB/LED/50W/6772lm/12/DALI/840/WH/OP								

