



A low glare architectural downlight with a round minimal bezel. Fitted with integral IP44 protective lens and a deep matt black bezel to minimise glare.

- A lumen output of 627lm or 811lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Colours: White or Black (/WH/BK)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with remote Emergency (/RME3/RME3-ST /RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Bezel Options: Black or White (/BK/WH)
- IP Rating: IP44
- Dimensions: (Diameter x Depth)
Ø85 x 95mm
- Cut Dimensions: (Diameter)
Ø81mm

Product	MID/BLT-C Recessed LED Downlight				
Light Source	LED				
System Power Luminaire lumens (4000K)	/6.7W 627lm		/8.2W 811lm		
Size Cut-out	Ø 85mm Ø 81mm				
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/827 2700k		/830 3000k		/840 4000k
Colour	/WH White			/BK Black	
Bezel Options	/BK Black Baffle			/WH White baffle	
Emergency	/RME3 Remote three hour maintained emer- gency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency	
To Specify: BLT-C LED, 6.7W, 4000k, 627lm LED downlight luminaire finished white supplied complete with control gear and a black bezel. Part code: MID/BLT-C/6.7W/627lm/STD/840/WH/BK					

