



**A cast aluminium LED IP65 amenity exterior luminaire available with various bezel options.**

- A range lumen outputs from 946-1951lm
- Colour Temperatures: 3000k - 4000k
- Colour: White, Grey or Black (/WH/GR/BK)
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Emergency Options(/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Mountings: Surface mounted as standard
- Diffuser options: Polycarbonate opal diffuser (/OP)
- Sensor: Microwave Presence detector (/MW)
- IP Rating: IP65
- Bezel options: Hood (/HD)
- Housing: Die cast aluminium body
- Dimensions: (Diameter x Depth) Ø351 x 130mm

Exterior

Product	MI/CASP Circular IP65 LED Luminaire			
Light Source	LED			
System Power Luminaire lumens (4000K)	/8.8W 946lm	/12.4W 1266lm	/13.6W 1488lm	/18.7W 1951lm
Size	Ø351mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k	
Colour	/BK Black	/GR Grey	/WH White	
Bezel Options	/HD Hood			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: CASPER LED, 18.7W, Ø351mm, 1951lm, 4000k, LED surface mounted finished black supplied with hood attachment and complete with standard control gear. Part code: MI/CASP/18.7W/1951lm/840/BK/HD				

