



**Low maintenance, affordable and efficient IP65 LED bulkhead luminaire. Designed with a unique replaceable gear tray and integral sensor options.**

- A range of lumen outputs of 1100lm or 1500lm
- Colour Temperature: 4000k
- Available with Dimming (/STD/DALI)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Diffuser: Opal (/OP)
- Mountings: Wall/Surface Mounting as standard
- Sensors: Available with microwave sensor for presence detection or corridor function (/MW/CDR)
- IP Rating: IP65 as standard
- Dimensions: (Diameter X Depth)  
Ø400 x 107mm

Product	MIS/CHALLENGER Surface LED circular			
Light Source	LED			
System Power	/15W 1100lm			/22W 1500lm
Size Depth	Ø370mm 100mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/WI Wireless Control	
Colour Temperature	/840 4000k			
Colour	/WH White			
Diffuser Options	/OP Opal Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: MIS CHALLENGER LED, 22W, 4000k, 1500lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/CHALLENGER/22W/1500lm/DALI/840/WH/OP				

Unique Hinged gear tray

