



The CLASS-E is a linear lighting luminaire that delivers bright, high-quality illumination, featuring a curved prismatic diffuser. With its minimalist design, suitable for schools, offices, retail areas, and hotels.

- A range of lumen outputs from 2600-5418lm
- Colour Temperatures: 3000k - 4000k - 5000k - 5700k
- Colour: White or Silver (/WH/SLV)
- Other RAL colours available upon request
- Available with Dimming (/STD/DALI)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3- PRO)
- Wireless Emergency (/ME3-WI)
- IP Rating: IP40
- IK Rating: IK08
- Mountings: Surface or Wire suspended (/SM/WS)
- Diffuser: Prismatic Diffuser, 120 degree beam angle (/MPO)
- Body Material: Aluminium
- Dimensions: (Length x Width x Height)
600/1200/1500 x 162 x 50mm

Product	MIS/CLASS-E Surface LED Linear			
Light Source	LED			
System Power Luminaire lumens (4000K)	/20W 2600lm	/33.5W 4443lm		/41W 5418lm
Size (L x W x H)	/6 600 x 162 x 50mm	/12 1200 x 162 x 50mm		/15 1500 x 162 x 50mm
Driver	/STD Non Dimming		/DALI DALI Dimming	
Colour Temperature	/830 3000k	/840 4000k	/850 5000k	/857 5700k
Colour	/WH White - RAL9016		/SLV Silver - RAL9006	
Diffuser Options	/MPO Prismatic Diffuser, 120 degree beam angle			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressa- ble emergency
To Specify: CLASS-E LED, 33.5W, 4000k, 4443lm, finished white, surface mounted and supplied complete with DALI control gear. Part code: MIS/CLASS-E/33.5W/4443lm/DALI/840/WH/MPO/SM				

CLASS-E
Prismatic Diffuser

