




The CO is a high-efficacy luminaire delivering 150 lm/W with a 120° symmetric optic even light distribution.

Pre-wired for fast emergency and compatible with self-test emergency systems. Ideal for warehouse applications.

- A range of lumen outputs from 15,000lm - 30,000lm
- Colour Temperatures: 4000k
- Colour: Black RAL9017 (/BK)
- Standard Non Dimming (/STD)
- Available with Emergency (/ME3/ME3-ST/)
- Mountings: Wire Suspended (/WS)
- Diffuser: Polycarbonate
- IP Rating: IP65
- Distribution: 120 Degree Symmetric Optic
- Housing: Die cast aluminium
- Dimensions: (Diameter x Height)
 - /100W - Ø227 x 103mm
 - /150W - Ø255 x 113mm
 - /200W - Ø280 x 113mm

Product	MI/CO Suspended Industrial Circular LED Luminaire		
Light Source	LED		
System Power Luminaire lumens (4000K)	/100W 15,000lm	/150W 22,500lm	/200W 30,000lm
Size	Ø227 x 103mm	Ø255 x 113mm	Ø280 x 113mm
Driver	/STD Non Dimming		
Colour Temperature	/740 4000k		
Mounting	/WS Wire Suspended		
Distribution	120 Degree Symmetric Optic		
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	
To Specify: CO Luminaire, 100W, with Ø227mm diameter, 15000lm, 4000k, Wire Suspended, finished black and supplied with standard control gear. Part code: MI/CO/100W/15000lm/STD/740/BK/WS			

Dimensions Diagram



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency
-------	--------------------	---------	--------	------	--------	--------------------	---------	-----------

How to Specify