



**A surface mounted stylish and compact circular IP65 bulkhead suitable for ceiling mount applications.**

- A lumen output of 390lm or 600lm
- Colour Temperature: 6500k
- Lens: Open Area (/OA/CL/HI-LEVEL)
- Colour: White RAL9016 (/WH)
- Emergency Options:
  - Three Hour Maintained (/ME3)
  - Three Hour Non Maintained (/NME3)
  - Three Hour Non Maintained Self-Test (/NME3-ST)
  - DALI Addressable Emergency (/NME3-PRO)
- Mounting: Surface Mounted
- Rated IP65
- Body constructed from retardant polycarbonate
- Dimensions: Diameter: Ø202mm Depth: 58mm

Product	MIS/EMLED/IP65 IP65 Standalone Emergency Luminaire			
Lamp	LED			
Lamp Power	/3W 390lm	/6W 600lm (/NME3 Only)		
Installation	MIS/C/ Surface Circular			
Colour Temperature	6500k			
Colour	/WH White-RAL9016			
Lens Options	/OA Open Area			
Emergency	/ME3 Three hour main- tained emergency	/NME3 Three hour non-maintained emergency	/NME3-ST Three hour non-maintained self test emergency	/NME3-PRO Three hour non-maintained DALI addressable emergency
To Specify: EMLED IP65 C LED, 3W, 6500k as standard, LED surface mounted circular finished white supplied complete with three hour non maintained emergency. Part code: MIS/EMLED/IP65/C/3W/WH/OA/NME3				

