



Recessed



**The FLATLINE-C is the latest in energy efficient modular lighting providing an aesthetically pleasing lighting solution to the workplace. Suitable for offices, open area offices, retail outlets, corridors and amenity areas.**

- A lumen output of 4135lm
- Colour Temperatures: 3000k - 4000k
- Colour: White (/WH)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Exposed Tee ceilings, Spring Tee and other ceiling options
- Mounting: Recessed
- Diffuser Options: Opal (/OP)
- Uniform illuminance across the opal diffuser
- Dimensions: (Diameter) Ø600mm
- Depth without driver 15mm, Depth with driver 42mm (Driver supplied rear mounted as standard)

Product	MIR/FLT-C Recessed LED Circular				
Light Source	LED				
System Power <small>Luminaire lumens (4000K)</small>	/46W 4135lm				
Size	Ø600mm				
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		
Colour	/WH White				
Diffuser Options	/OP Opal				
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency	
To Specify: FLATLINE-C LED, 46W, 4000k, 4135lm LED modular recessed finished white supplied complete with DALI control gear and opal diffuser. Part code: MIR/FLT-C/46W/4135lm/DALI/840/WH/OP					

