



An IP42 Flat bay luminaire designed for manufacturing or storage areas. Suitable for warehouses, retail stores, hangers, exhibition, concert halls and high ceiling premises generally.

- A range of lumen outputs from 13,400-70,000lm
- Colour Temperatures: 4000k -5000k - 6500k
- Colour: White (/WH)
- Available with Dimming (/STD/DALI/SDIM)
- Sensor Attachment Available (/MW)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless (/WI) & Wireless Emergency available (/ME3-WI)
- Integral LED Meanwell driver
- Mountings: Wire suspended, Chain suspension or surface mounted (/WS/CS/SM)
- IP Rated: IP42
- Beam Angles: Narrow, Medium, Wide, Diffuse or Asymmetric (/NB/MB/WB/DB/AB)
- Body: Aluminium body with Polycarbonate Optical Cover
- Dimensions: (Length x Width x Height) 265-1309 x 140 x 87.5mm

Product	MIFB Industrial LED Luminaire				
Light Source	LED				
Length	/3 265mm	/5 526mm	/7 767mm	/10 1048mm	/13 1309mm
System Power <small>Luminaire lumens (4000K)</small>	/82W 13,400lm	/165W 26,100lm	/248W 40,000lm	/330W 52,200lm	/440W 70,000lm
Weight	2.4Kg	3.7Kg	5.1Kg	7.1Kg	9.2Kg
Driver	/STD Non Dimming		/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/840 4000k		/850 5000k		/865 6500k
Reflector Options	/NB Narrow Beam 30°x30°	/MB Medium Beam 50°x50°	/WB Wide Beam 70°x70°	/DB Diffused Beam 120°x120°	/AB Asymmetric Beam
Emergency	/ME3 3 hour maintained emergency	/ME3-ST 3 hour maintained self test emergency	/ME3-PRO 3 hour DALI addressable emergency		/ME3-WI 3 hour Wireless emergency
To Specify: MIFB LED, 1048mm long, 330W, 52,200lm, with Standard Driver, 4000k, Wide Beam and Wire Suspended. Part code: MIFB/10/330W/STD/840/WB/WS					

