

FLED 84W & 121W



Post Top



Side Entry



Wall Stirrup



Wall Mount



Wall Plate

The FLED 84W & 121W is an IP66 robust post top and wall mounted floodlight with a clear lens and black powder coat finish.

- A lumen output of 10,109lm or 14,644lm
- Colour Temperature: 3000k - 4000k - 5000k
- Lens: Tempered clear flat glass
- Colour: Black as standard (/BK)
- Standard Non Dimming (/STD)
- Emergency not available
- Mounting: 76-102mmØ Post Top Spigot, Stirrup, Side Entry, Wall Mount, Wall Plate, Wall Swivel
- Sensor: Photocell (/PC)
- IP Rating: IP66
- Black powder coat polyester finish over epoxy powder
- Housing: Die cast aluminium and front frame. Integral heat sink
- Dimensions: (Length x Width x Depth) 381 x 340 x 92mm

Exterior

Product	MI/FLED IP66 LED Floodlight Luminaire					
Light Source	LED					
System Power <small>Luminaire lumens (4000K)</small>	/84W 10109lm			/121W 14644lm		
Size	381x 340 x 92mm					
Distribution	ASYM-1	ASYM-2	ASYM-3	ASYM-4	SYM-1	SPOT-1
Driver	/STD Non Dimming					
Colour Temperature	/830 3000k		/840 4000k		/850 5000k	
Mounting	/PT Post Top	/SE Side Entry	/WMST Wall Stirrup	/WMB Wall Mount	/WMP Wall Plate	/WMSW Wall Swivel
To Specify: FLOODLIGHT LED, 84W, 10109lm, 4000k, Asymmetric-1 Distribution with Wall Mounted luminaire supplied with standard integral control gear. Part code: MI/FLED/84W/10109lm/STD/840/ASYM-1/WMB						

