



The Galaxy High Out is an IK10 and IP66-rated bulkhead designed for high ceilings. It delivers up to 316 lumens in mains operation and 1001 lumens in DALI-2 emergency mode, powered by energy-efficient LiFePO₄ batteries.

- A lumen output of 1001lm
 - Colour Temperature: 4000k
 - Colour: White (/WH)
 - Emergency Options:
 - Three Hour Maintained (/ME3),
 - Three Hour Non Maintained (/NME3),
 - Self Test (/ME3-ST),
 - DALI Addressable Emergency (/ME3-PRO)
 - Mountings: Surface as standard (/SM)
- Diffuser: Prismatic Lens
 - IP Rating: IP66
 - IK Rating: Ik10
 - Self-adhesive universal legend kit for exit sign (/ULK)
 - Body constructed from retardant polycarbonate
 - Dimensions: (Length x Width x Depth)
370 x 140 x 100mm

Product	GALAXY High Out A Surface Mounted High Output Bulkhead			
Light Source	LED			
System Power	/13.2W 1001lm (with maintained emergency)			
Size	370 x 140 x 100mm (without exit sign)			
Driver	/STD Non Dimming			
Colour Temperature	4000k			
Colour	/WH White			
Emergency	/NME3 Three hour non maintained emergency	/NME3 Three hour non-maintained emergency	/NME3-ST Three hour non maintained self test emergency	/NME3-PRO Three hour non DALI addressable emergency
To Specify: GALAXY HO LED, 13.2W, 4000k as standard, LED surface mounted finished white supplied complete with standard control gear, and three hour non-maintained emergency. Part code: MI/GAL-HO/LED/13.2W/WH/NME3				

Overall Dimensions For GALAXY-HO

