



A high quality, low glare and general purpose luminaire ideal for classrooms and corridors.

- A range of lumen outputs from 3000-5750lm
- Colour Temperatures: 3000k - 4000k
- Available with Dimming (/STD/DALI/SDIM/1-10V)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Mountings: Surface or Wire suspended (/SM/WS)
- Steel body with BESA fixings
- Dimensions: (Length x Width x Height)
 - /6 - 630 x 210 x 70mm
 - /12 - 1190 x 210 x 70mm
 - /15 - 1490 x 210 x 70mm

Product	MIS/GUIDO2 Surface linear LED			
Light Source	LED			
System Power <small>Luminaire lumens (4000K)</small>	/25W 3000lm	/35W 4025lm	/50W 5750lm	
Size	/6 630mm	/12 1190 x 210mm		/15 1490 x 210mm
Driver	/STD Non Dimming	/1-10V 1-10V Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Wireless Control	/WI Wireless Control			
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White			
Diffuser Options	/OP Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emer- gency
To Specify: MIS GUIDO2 LED, 1190mm, 50W, 5750lm, 4000k, surface linear finished white. Wireless Control with DALI control gear and opal diffuser. Part code: MISGUIDO2/12/50W/5750lm/DALI/WI/840/WH/OP				

Installation

