



**A high quality, low glare and general purpose luminaire  
ideal for classrooms and corridors.**

- A range of lumen outputs from 3012-5760lm
  - Colour Temperatures: 3000k - 4000k
  - Available with Dimming (/STD/DALI/SDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Steel body with anti-tamper screw fixing end caps
- Surface mounted or Wire suspended (/SM/WS)
- Dimensions: 1175/1483 x 184 x 85mm

Product	MIS/GUIDO Surface LED linear			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/28W 3012lm	/48W 4740lm	/32W 3631lm	/52W 5760lm
Size	/12 1175 x 184mm		/15 1483 x 184mm	
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White			
Diffuser Options	/RD Reeded Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: MIS GUIDO LED, 28W, 4000k, 3012lm LED surface linear finished white supplied complete with DALI control gear and opal diffuser. Part code: MISGUIDO/LED/28W/3012lm/12/DALI/840/WH/RD				

