



**The HI-LED range is designed for use in open areas where an even uniformity is required. Suitable for narrow aisles, general warehousing, garages and areas where a high lumen output and shallow profile body combination is required.**

- A range of lumen outputs from 12406-26952lm
- Colour Temperatures: 3000k - 4000k
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Optional daylight sensor available (/DS)
- Mountings: Surface mounted as standard, Chain suspension, Wire suspension, Drop rods or Trunking mounted (/CS/WS/DR/TM)
- Diffuser: Opal as standard
- Steel body finished white
- Dimensions: (L x W x H) 750/1200/1750 x 420 x 70mm
- 5 year system warranty

Product	MIHILED Low Bay LED			
Light Source	LED			
System Power Luminaire lumens (4000K)	/95.5W 12406lm	/166.7W 21384lm	/211.6W 26952lm	
Size	/07 750mm	/12 1200mm	/17 1750mm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White			
Diffuser Options	/OP Opal			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: HILED , 95.5W, 750mm, 12406lm, 4000k, LED surface mounted finished white supplied complete with standard control gear. Part code: MIHILED/07/95.5W/12406lm/STD/840/WH/OP				

