



ILS/A1/6W



ILS/A1/9W



ILS/A1/13W &amp; ILS/A1/18W

**The small adjustable ILS A1 downlight is a competitive, interchangeable and architectural LED downlight system.**

**An alternative light engine to an MR16 or GU10 lamp.**

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: White, Silver, Grey or Black
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- CRI > 90 Available (/930/940)
- Adjustable
- Offset from bezel
- Dimensions: (Diameter x Depth) see page 25  
Ø90 x 64mm, 82mm, 86mm
- Cut-out Dimension: (Diameter) Ø75mm
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating

Product	MID/ILS/A1 Recessed ILS A1 Downlight				
LED	/6W	/9W	/13W	/18W	
System Power Luminaire lumens (4000K)	8W 723lm	11W 1219lm	15W 1494lm	21W 2049lm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		
Colour	/WH White	/SLV Silver	/GR Grey	/BK Black	
Beam Angle Options	/22D 22 Degree		/36D 36 Degree		/60D 60 Degree
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency	
To Specify: MID ILS A1 9W, 60 degree beam angle, 4000k, 1219lm LED downlight, with an ILS bezel attachment; A1 in white. Part code: MID/ILS/A1/9W/1219lm/STD/840/WH/60D					

