



**The ILS CELL3 is a range of interchangeable trimmed and plaster-in bezel options and has a range of reflector colours available. The CELL3 can be used with the ILS 6W and 9W engine wattages.**

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: White or Black (/WH/BK)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- CRI90 as standard (/930/940)
- Reflector colours: Range of reflectors shown above
- Dimensions: (Length x Width x Depth)  
Trimmed: /T - 207 x 78 x 72mm (6W), 98mm (9W)  
Plaster-in: /P - 207 x 78 x 72mm (6W), 98mm (9W)
- Cut-Out Dimensions: (Length x Width)  
Trimmed: /T - 198 x 68mm, Plaster-in: /P - 200 x 72mm
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating

Product	MID/ILS/C3/T ILS Cell3 Trimmed			MID/ILS/C3/P ILS Cell3 Plaster-in		
LED	/6W			/9W		
System Power Luminaire lumens (4000K)	8W 800lm			10W 1160lm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control	
Colour Temperature	/930 3000k			/940 4000k		
Bezel Colour	/WH White			/BK Black		
Beam Angle Options	/22D 22 Degree		/36D 36 Degree		/60D 60 Degree	
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency		
To Specify: MID ILS C3 Plaster-in 9W, 60 degree beam angle, 4000k, 1160lm LED downlight, with an ILS bezel attachment; C3 in white with black trim. Part code: MID/ILS/9W/1150lm/STD/940/WH/60D/BK						

