



The ILS CELL3 is a range of interchangeable trimmed and plaster-in bezel options and has a range of reflector colours available. The CELL3 can be used with the ILS 6W and 9W engine wattages.

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: White or Black (/WH/BK)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- CRI > 90 Available (/930/940)
- Reflector colours: Range of reflectors shown above
- Dimensions: (Length x Width x Depth)
Trimmed: /T - 207 x 78 x 72mm (6W), 98mm (9W)
Plaster-in: /P - 240 x 112 x 72mm (6W), 98mm (9W)
- Cut-Out Dimensions: (Length x Width)
Trimmed: /T - 198 x 68mm, Plaster-in: /P - 200 x 72mm
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating

Product	MID/ILS/C3/T ILS Cell3 Trimmed			MID/ILS/C3/P ILS Cell3 Plaster-in		
	LED	/6W			/9W	
System Power <small>Luminaire lumens (4000K)</small>	8W 723lm			11W 1219lm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control	
Colour Temperature	/830 3000k			/840 4000k		
Bezel Colour	/WH White			/BK Black		
Beam Angle Options	/22D 22 Degree		/36D 36 Degree		/60D 60 Degree	
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency		/RME3-WI Remote three hour Wireless addressable emergency	
To Specify: MID ILS C3 Plaster-in 9W, 60 degree beam angle, 4000k, 1219lm LED downlight, with an ILS bezel attachment; C3 in white with black trim. Part code: MID/ILS/9W/1219lm/STD/840/WH/60D/BK						

