

# ILS G1 MATRIX CENTERVIEW



ILS/G1/9W/BK

**The adjustable ILS G1 MATRIX downlight is a competitive, interchangeable and architectural LED adjustable downlight system. An alternative light engine to an MR16 or GU10 lamp.**

- A range of lumen outputs from 650-1800lm
- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: White, Grey or Black
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Adjustable
- Dimension: (Length x Width x Depth)  
110 x 110 x 97mm(6W), 115mm(9W), 119mm(13 & 18W)
- Cut-out Dimension: (Length x Width)  
100x100mm
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating
- CRI > 90 Available

Product	MID/ILS/G1/MATRIX Recessed ILS G1 Downlight				
LED	/6W	/9W	/13W	/18W	
System Power Luminaire lumens (4000K)	8W 723lm	11W 1219lm	15W 1494lm	21W 2049lm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		
Colour	/WH White		/GR Grey	/BK Black	
Beam Angle Options	/22D 22 Degree		/36D 36 Degree	/60D 60 Degree	
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency	
To Specify: MID ILS G1 MATRIX 9W, 60 degree beam angle, 4000k, 1219lm LED downlight, with an ILS bezel attachment; G1 in white. Part code: MID/ILS/G1/MATRIX/9W/1219lm/STD/840/WH/60D					

