



ILS/S6/6W

ILS/S6/9W

ILS/S6/13W & ILS/S6/18W

The adjustable ILS S6 downlight is a competitive, interchangeable and architectural LED downlight system. An alternative light engine to an MR16 or GU10 lamp.

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: White, Silver, Grey or Black
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- CRI > 90 Available (/930/940)
- Adjustable
- Dimensions: (Length x Width x Depth) see page 25
110 x 110 x 68mm, 93mm, 98mm
- Cut-out Dimension: (Diameter) Ø95mm
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating

| Product | MID/ILS/S6 Recessed ILS S6 Downlight | | | | |
|--|--|--|---|--|-------------------------|
| LED | /6W | /9W | /13W | /18W | |
| System Power Luminaire lumens (4000K) | 8W 723lm | 11W 1219lm | 15W 1494lm | 21W 2049lm | |
| Driver | /STD Non Dimming | /DALI DALI Dimming | /SDIM Switch Dimming | /MDIM Mains Dimming | /WI Wireless Control |
| Colour Temperature | /830 3000k | | /840 4000k | | |
| Colour | /WH White | /SLV Silver | /GR Grey | /BK Black | |
| Beam Angle Options | /22D 22 Degree | | /36D 36 Degree | | /60D 60 Degree |
| Emergency | /RME3 Remote three hour maintained emergency | /RME3-ST Remote three hour maintained self test emergency | /RME3-PRO Remote three hour DALI addressable emergency | /RME3-WI Remote three hour Wireless addressable emergency | |
| To Specify: MID ILS S6 9W, 60 degree beam angle, 4000k, 1219lm LED downlight, with an ILS bezel attachment; S6 in white. Part code: MID/ILS/S6/9W/1219lm/STD/840/WH/60D | | | | | |

