



White Reflector  
/WHR



Grey Reflector  
/GRR



Gold Reflector  
/GDR



Black Reflector  
/BKR

**A high-quality rectangular surface mounted LED with interchangeable decorative rings designed for a variety of lighting applications.**

- A lumen outputs of 750lm or 950lm
- Colour Temperatures: 3000k - 4000k
- Beams Lens: 24° or 40° (/24D/40D)
- Colours: White or Black (/WH/BK)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/ME3-WI)
- Mountings: Surface mounted or Wire suspended (/SM/WS)
- Reflector Colours: White, Gold, Black or Grey (WHR/GDR/BKR/GRR)
- CRI80 as standard, CRI90 Available
- Dimensions: (Length x Width x Height)
  - /2x2 - 151 x 81 x 81mm
  - /1x5 - 141 x 158 x 50mm

Product	MIS LED-GO Surface mounted LED				
LED	/9W		/11W		
Lamp Power <small>Luminaire lumens (4000K)</small>	11W 750lm		13W 950lm		
Size <small>(L x W x H)</small>	/2x2 151 x 81 x 81mm		/1x5 141 x 158 x 50mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		
Reflector Colours	/WHR White Ring	/GDR Gold Ring	/GRR Grey Ring	/BKR Black Ring	
Beam Lens	/24D 24 Degrees		/40D 40 Degrees		
Colour	/WH White		/BK Black		
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three DALI addressable emergency	/RME3-WI Remote three hour wireless addressable emergency	
To Specify: LED GO 2 by 2, 9W, 4000k, CRI80, 750lm LED Surface Mounted, black housing finish and Gold reflector Ring, with 20 degree narrow beam lens and Standard non dimming. Part code: MIS/GO/2x2/9W/750lm/STD/840/BK/20D/GDR/SM					

1x5 LED-GO Version  
in /BK/GDR

