



The LO-X is an explosion proof LED luminaire which is ideal for extreme situations. Certified for hazardous area classification zone 1, 2, 21 & 22

- A range of lumen outputs from 2570 - 10050lm
- Colour Temperatures: 4000k
- Colour: White RAL9003 (/WH)
- Standard Non Dimming (/STD)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Hazardous Area Classification: Zone 1, 2, 21 & 22
- Mountings: Ceiling Mounting, Wire Suspended or Recessed with frame as standard (/SM/WS/R)
- Diffuser: Tempered safety glass
- IP Rating: IP66
- IK Rating: IK10
- Available with 1 Phase and 3 Phase through wiring
- Dimensions: (Length x Width x Depth)
 - /7 - 730 x 300 x 115mm
 - /13 - 1300 x 300 x 115mm

Product	LO-X Industrial LED Luminaire			
Light Source	LED			
System Power Luminaire lumens (4000K)	/24W 2570lm	/48W 5150lm	/48W 5020lm	/96W 10050lm
Size	/7 730 x 300 x 115mm		/13 1300 x 300 x 115mm	
Driver	/STD Non Dimming			
Colour Temperature	/840 4000k			
Mounting	/SM Ceiling Mounting	/WS Wire Suspended	/R Recessed	
Reflector	Satiated tempered safety glass			
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	
To Specify: LO-X LED, Length 730mm, 24W, 2570lm, 4000k, LED, wire suspended and supplied with standard control gear. Part code: LO-X/7/24W/2570lm/STD/840/GR/WS				

Fitting attachments

/CM - Ceiling mounted



/R - Recessed



/WS - Wire Suspension



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3	Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency
How to Specify									