



The MEMI-2 is an IP65 decorative and robust wall mounted amenity luminaire with a clear lens and black powder coat finish. A high output option in comparison to the MEMI.

- A range lumen outputs from 2467-5344lm
- Colour Temperature: 4000k - 5000k
- Lens: Tempered clear prismatic glass lens
- Colours: Black (/BK)
- Standard Non Dimming (/STD)
- Emergency Options(/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Distribution: Symmetrical or Asymmetric (/SYM/ASY)
- Mountings: Wall mounted
- IP Rating: IP65
- Black powder coat polyester finish over chromate conversion coating as standard
- Housing: Die cast aluminium housing
- Dimensions: (L x W x H) 460 x 229 x 233mm

Exterior

| | | | | |
|--|---|--|---|--|
| Product | MI/MEMI-2 Wall IP65 LED Luminaire | | | |
| Light Source | LED | | | |
| System Power <small>Luminaire lumens (5000K)</small> | /26W 2467lm (SYM), 2615lm (ASY) | | /52W 4613lm (SYM), 5344lm (ASY) | |
| Size | 460 x 229 x 233mm | | | |
| Driver | /STD Non Dimming | | | |
| Colour Temperature | /840 4000k | | /850 5000k | |
| Optics | /SYM Symmetrical Distribution (4000k or 5000k) | | /ASY Asymmetric Distribution (5000k only) | |
| Colour | /BK Black | | | |
| Emergency | /ME3 Three hour main- tained emergency | /ME3-ST Three hour main- tained self test emergency | /ME3-PRO Three hour DALI addressable emergency | /ME3-WI Three hour Wireless addressable emergency |
| To Specify: MEMI-2 LED, 52W, 4631lm, 4000k, LED wall mounted luminaire finished black complete with standard integral control gear. Part code: MI/MEMI-2/52W/4631lm/STD/840/BK | | | | |

MEMI-2 Wall Mounted

