


# MID130 SURF



**A high quality LED surface mounted LED downlight, or as a pendant. For suspension or direct mounting on to solid ceiling systems, or where the ceiling void is too shallow to accept a recessed downlight.**

- A range of lumen outputs from 1060-2420lm
  - Colour Temperatures: 3000k - 4000k
  - Colours: White RAL9016, Brilliant White RAL9016, Black RAL9005 or Grey RAL9006 (/WH/BWH/BK/GR)
  - Available with Dimming (/STD/DALI/SDIM)
  - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Mountings: Surface mounted or Wire suspended (/SM/WS)
  - Reflector Options: Faceted Reflector, Satin Etched, Highly Specular (/FR/SE/HS)
  - Dimensions: (Diameter x Depth)  
Ø150 x 165mm

Product	MID130/SURF Surface MID130 Downlight		
Light Source	LED		
System Power <small>Luminaire lumens (4000K)</small>	/8W 1060lm	/13.8W 1730lm	/19.1W 2420lm
Size	Ø150mm x 165mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dim
Colour Temperature	/830 3000k		/840 4000k
Body Colour	/WH White RAL9010	/BWH Brilliant White (RAL 9016)	/BK Black RAL9005 /GR Grey RAL9006
Reflector Options	/FR Faceted Reflector	/SE Satin Etched	/HS Highly Specular
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: MID130 SURF LED, 13.8W, 4000k, 1730lm LED downlight finished white supplied with faceted reflector and standard control gear. Part code: MID130/SURF/13.8W/1730lm/STD/840/WH/FR			



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

- Style
- Range abbreviation
- Wattage
- Lumens
- Size
- Driver
- Colour Temperature
- Options
- Emergency