


Clear /CL



Opal /OP



Clear Halo /CLH



Clear Opal /OPH

**A high quality LED downlight with a highly specular reflector and square design creates a refined, flawless look throughout allowing it to be personalised to taste with its different Bezels.**

- A range of lumen outputs from 1104-5001lm
- Colour Temperatures: 3000k - 4000k
- Available with Dimming (/STD/DALI)
- Wireless (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Bezel Options: Clear, Opal, Clear Halo or Opal Halo (/CL/OP/CLH/OPH)
- Dimensions: (Length x Width x Height)  
170 x 170 x 112mm
- Cut Out Dimensions: (Length x Width)  
140 x 140mm

Product	MID200-SQ Surface MID140 Downlight							
Light Source	LED							
System Power Luminaire lumens (4000K)	/9.5W 1104lm	/11.2W 1130lm	/17.5W 1968lm	/20.1W 2160lm	/27W 3024lm	/30.5W 3203lm	/46.6W 5001lm	
Size Cut-out	170 x 170 x 112mm (LxWxH) 140 x 140mm							
Driver	/STD Non Dimming		/DALI DALI Dimming			/WI Wireless Control		
Colour Temperature	/830 3000k				/840 4000k			
Bezel Options	/CL Clear	/OP Opal	/CLH Clear Halo		/OPH Opal Halo			
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency		/RME3-WI Remote three hour Wireless addressa- ble emergency			
To Specify: MID200-SQ, 11.2W, 4000k, 1130lm LED downlight finished white supplied with Clear acrylic and standard control gear. Part code: MID200-SQ/11.2W/1130lm/STD/840/CL								

