



IP54 Clear Cover  
(/CL/IP54)



IP65 Clear Cover  
(/CL/IP65)



IP65 Opal Cover Polycarbonate  
(/OP/P/IP65)



IP65 Clear Cover Polycarbonate  
(/CL/P/IP65)

**A high quality LED downlight providing flexibility through interchangeable decorative and IP rated attachments.**


- A range of lumen outputs 1190-4949lm
  - Colour Temperatures: 3000k - 4000k - Tunable White
  - Available with Dimming (/STD/DALI/SDIM/MDIM)
  - Wireless Control (/WI)
  - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
  - Wireless Emergency (/ME3-WI)
  - Bezel Options: Brilliant White RAL9016 or request for any specified RAL colour bezel (/WH)
  - Reflector Options: Satin etched as standard, or Faceted Reflector (/SE/FR)
  - IP Rating: IP20, IP54 or IP65 depending on bezel
  - Dimensions: (Diameter x Depth)  
Ø232 x 140mm
  - Cut-out Dimensions: Ø213mm - Ø222mm
- Please note:** All IP65 Covers are White RAL9010 as standard.

Product	MID240/LED Recessed MID240 Downlight				
Light Source	LED				
System Power <small>Luminaire lumens (4000K)</small>	/9.7W 1190lm	/17.4W 2062lm	(TWH)- /17.7W 1900lm	/30.5W 3169lm	/46.6W 4949lm
Size Cut-out	Ø232 x 140mm Ø213 - Ø222mm				
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control	
Colour Temperature	/830 3000k		/840 4000k		/TWH Tunable White
Bezel Colour	/WH White-RAL9016				
Reflector Options	(/FR) Faceted		(/SE) Satin Etched		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency	
To Specify: MID240 LED, 9.7W, 4000k, 1190lm LED downlight finished white supplied with satin etched reflector, DALI control gear and an IP54 Clear Cover. Part code: MID240/9.7W/1190lm/DALI/840/WH/SE/CL/IP54					

Reflector Options



Satin  
Etched  
(/SE)



Faceted  
Reflector  
(/FR)

