


White Plaster-in
/P/WH



Grey and Black
/GR/BKR



Black and Gold
/BK/GDR



Black and Black
/BK/BKR

A stylish linear downlight, available in 10 and 5 Lights with fixed or plaster-in bezel versions available in a range of bezel and reflector colours.

- A lumen output of 1050lm or 2100lm
- Colour Temperatures: 3000k - 4000k
- Beams Angles: 10°, 15° or 50° (10D/15D/50D)
- Colours: White, Grey or Black (/WH/GR/BK)
- Available with Dimming (/STD/DALI)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Reflector Colours: White, Black or Gold (/WHR/BKR/GDR)
- Trimless Plaster-in bezel version (/P)
- IP Rating: IP44
- CRI80 as standard, CRI90 Available
- Dimensions: (Length x Width x Height)
330 x 50 x 62mm
- Cut out dimensions: (Length x Width)
323 x 41mm

Product	MIDL10 Downlight			
Light Source	LED			
System Power <small>Luminaire lumens (4000K)</small>	/13W 1050lm		/23W 2100lm	
Size <small>(L x W x H)</small>	330mm x 50mm x 62mm			
Driver	/STD Non dimming	/DALI DALI Dimming	/WI Wireless Control	
Colour Temperature	/830 3000k		/840 4000k	
Colours	/WH White	/BK Black	/GR Grey	/P Plaster-in
Reflector Colours	/WHR White Reflector		/BKR Black Reflector	/GRR Grey Reflector
Beam Angle	/10D 10 Degrees		/15D 15 Degrees	/50D 50 Degrees
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: MIDLinear10, 13W, 4000k, CRI80, 1050lm LED downlight, a plaster-in black finish reflector, with 15 degree narrow beam lens and DALI control gear. Part code: MIDL10/13W/1050lm/DALI/840/BK/15D/BKR/P				

Side Profile View
Dimensions

