



White Plaster-in
/P/WH



Grey and Black
/GR/BKR



Black and Gold
/BK/GDR



Black and Black
/BK/BKR

A stylish linear downlight, available in 10 and 5 Lights with fixed or plaster-in bezel versions available in a range of bezel and reflector colours.

- A lumen output of 525lm or 1050lm
 - Colour Temperatures: 3000k - 4000k
 - Beam Angles: 10°, 15° or 50° (10D/15D/50D)
 - Colours: White, Grey or Black (/WH/GR/BK)
 - Available with Dimming (/STD/DALI)
 - Wireless Control (/WI)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Wireless Emergency (/ME3-WI)
- Reflector Colours: White, Black or Gold (/WHR/BKR/GDR)
 - Trimless Plaster-in bezel version (/P)
 - IP Rating: IP44 as standard, IP65 available
 - CRI80 as standard, CRI90 Available
 - Dimensions: (Length x Width x Height)
175 x 50 x 62mm or 195 x 80 x 62mm
 - Cut out dimensions: (Length x Width)
166 x 41mm & 183 x 70mm

Product	MIDL5 Downlight			
Light Source	LED			
System Power Luminaire lumens (4000K)	/7W 525lm		/13W 1050lm	
Size (L x W x H)	/IP65 195mm x 80mm x 62mm		/IP44 175mm x 50mm x 62mm	
Driver	/STD Non dimming	/DALI DALI Dimming		/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k	
Colours	/WH White	/BK Black	/GR Grey	/P Plaster-in
Reflector Colours	/WHR White Reflector		/BKR Black Reflector	/GRR Grey Reflector
Beam Angle	/10D 10 Degrees		/15D 15 Degrees	/50D 50 Degrees
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: MIDLinear5, 13W, 4000k, CRI80, 1050lm LED downlight with white bezel finish and gold reflectors with 10 degree narrow beam lens, IP65 and DALI control gear. Part code: MIDL5/13W/1050lm/DALI/840/WH/10D/GDR/IP65				

