

MILEDEX V2



The MILEDEX Version 2 is a n Ultra-slim LED luminaire with excellent perform. Its designed for wall mounting and has a welded steel housing frame for even light distribution .

- Colour Temperature: 4500k
- Colour: White (/WH)
- Emergency Options:
Three Hour Maintained (/ME3),
Three Hour Non Maintained (/NME3),
Self Test (/ME3-ST),
DALI Addressable Emergency (/ME3-PRO)
- If ME3-WI is required please speak to Technical
- Single sided
- Viewing Distance: 25m
- IP Rating: IP20 as standard
- Mounting: Surface mounted
- Supplied with EN7010 format legends as standard.
BS5499 Format legends available upon request
- Body constructed from steel with PMMA legend panel
- Dimension: (Length x Height x Depth)
315 x 190 x 30mm

Product	MILEDEX Version 2 Ultra-slim LED single and double exit sign			
Light Source	LED			
System Power	/3.1W			
Size	315 x 190 x 30mm			
Driver	/STD Non Dimming			
Colour Temperature	4500k			
Colour	/WH White			
Emergency	/ME3 Three hour main- tained emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: MILEDEX V2 3.1W, 4500k as standard, LED surface mounted finished white supplied complete with standard control gear, arrow down legend and three hour non-maintained emergency. Part code: MILEDEX/V2/LED/3.1W/WH/NME3/AD				

Legend Options

(AU) - Arrow Up



(AR) - Arrow Right



(AL) - Arrow Left



(AU) - Arrow Down



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency
-------	--------------------	---------	--------	------	--------	--------------------	---------	-----------