MINICAN-C

The MINICAN-C is a modern, cylindrical surface-mounted or suspended LED luminaire available in a range of heights to suit various design requirements and architectural applications.

- A range of lumen outputs from 645-1440lm
- Colour Temperatures: 3000K - 4000K
- Colour: Black, Grey and White (/BK/GR/WH)
- Standard non dimming
- Contact Technical to confirm requirements of DALI and Wireless Control for this product
- Mountings: Surface mounted or Wire suspended (/SM/WS)
- Diffusers: Clear Reflector, Faceted Reflector (/CL/FR)
- IP Rating: IP20
- Aluminium powder exterior
- Dimensions: (Diameter x Height)

  Ø90 x *95mm,*120mm, 160mm, 180mm, 250mm

  Remote control gear due to smaller body sizes

Product	MID/MINICAN-C Surface or Suspended Circular MiniCan				
Light Source	LED				
System Power Luminaire lumens (4000K)	/7W 645lm	/10W 829lm	/18W 1440lm		
Height	*/95mm	*/120mm	/160mm	/180mm	/250mm
Driver	/STD Non Dimming				
Colour Temperature	/830 3000K	/840 4000K			
Colour	/BK Black	/GR Grey	/WH White		
Diffuser options	/FR Faceted Reflector	/CL Clear Reflector			
Emergency	n/a				

To Specify: MiniCan-C, 7W, 4000K, CRI80, 645lm LED surface light with black housing finish, 95mm in height with standard non dimming. Part code: MID/MINICAN-C/95mm/7W/645lm/STD/840/BK

Section View
Dimensions



01268 725086 | www.midlighting.co.uk | sales@midlighting.co.uk

Due to ongoing research and development specifications are subject to change without prior notice. Some availability subject to minimum order. All luminaire lumens are 4000k colour temperature readings.