



**An IP65 rated (front) LED luminaire. Ideal for use in environments such as laboratories, hospitals, bathrooms, kitchens, and clean room environments. Designed to integrate with specific ceiling systems as well as standard lay-in and concealed grid ceilings.**

- A range of lumen outputs from 4004-8008lm
- Colour Temperatures: 3000k - 4000k - 5000k - Tunable White (TWH)
- Available with Dimming (/STD/DALI/SDIM)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Wire suspended or surface mounted options available
- Exposed Tee ceilings, Spring Tee and other ceiling options available
- Diffuser Options: Polar White / Microprism / Lumieo Panel (/PW/MPO/MPOLP)
- Front and rear IP rated options available. IP65 front rating as standard, IP54 and IP65 rear available (/IP54R/IP65/IP65R)
- Additional lumen and wattage options available. Please contact our technical department for details.
- Dimensions: 600 x 600 x 91mm, 1200 x 300 x 95mm, 1500 x 300 x 91mm, 1200 x 600 x 95mm
- 5 year system warranty
- Refer to page 89 for ceiling system options

Product	MIR700 Recessed LED IP65 Modular			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/33.2W 4004lm	/33.2W 4004lm	/41.6W 5005lm	/66.4W 8008lm
Size	/66 600 x 600mm	/123 1200 x 300mm	/153 1500 x 300mm	/126 1200 x 600mm
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k	/850 5000k	/TWH Tunable White
Bezel Colour	/WH White			
Diffuser Options	/PW Polar White	/MPO Micro Prismatic Optic		/MPOLP MPO with Lumieo
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: MIR700 LED, 33.2W, 4000k, 4004lm LED modular recessed finished white supplied complete with DALI control gear, polar white diffuser and IP65 rated. Part code: MIR700/LED/33.2W/4004lm/66/DALI/840/WH/PW/IP65				

