




**A general purpose surface LED luminaire ideal for circulation areas.**

Surface & Suspended

- A range of lumen outputs from 941-2736lm
- Colour Temperatures: 3000k - 4000k
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Diffuser: Opal (/OP)
- Mountings: Surface as standard Wire suspended (/SM/WS)
- Microwave sensor and presence detector for corridor function available for circulation areas (/MW/CDR)
- Dimensions: (Diameter x Depth)  
Ø425 x 114mm

Product	MIS800 Circular Surface LED			
Light Source	LED			
System Power <small>Luminaire lumens (4000K)</small>	/8W 941lm	/11W 1275lm	/16.5W 1840lm	/22.1W 2856lm
Size Depth	Ø425mm 114mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White			
Diffuser Options	/OP Opal Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: MIS800 LED, 26W, 4000k, 2736lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS800/26W/2736lm/DALI/840/WH/OP				



MIR/RANGE/5W/LM/SIZE/DIM/840/OPT/ME3

How to Specify

- Style
- Range abbreviation
- Wattage
- Lumens
- Size
- Driver
- Colour Temperature
- Options
- Emergency