



**A cost effective, reinforced opal polycarbonate vapour resistant luminaire supplied with stainless steel retention bracket for body, suitable for all indoor and external under cover applications only.**

- A range of lumen outputs from 1500-6490lm
- Colour Temperatures: 4000k
- Available with Dimming (/STD/1-10V/DALI/SDIM)
- Wireless Emergency (/ME3-WI) & Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Mounting: Screw fix mounted as standard. Stainless steel fixing clips are available or Wire Suspension (/SSC/WS)
- Diffuser: Frosted opal polycarbonate diffuser
- IP Rating: IP65
- Standard Driver option has the facility to set 3 light outputs via dipswitch
- Suitable for all indoor and external under cover applications only.
- Dimensions: Length - 665/1275/1575mm, Width - 84/134mm, Depth - 98.5mm,
- 5 year system warranty for LED

Product	MIVP-ECO Linear LED Vapour Proof Luminaire					
Light Source	LED					
System Power Luminaire lumens (4000K)	/11.5W 1500lm	/20.9W 2590lm	/27.6W 3780lm	/39W 5190lm	/34.5W 4730lm	/48.9W 6490lm
Size	/6 665 x 134mm		/12 1275 x 84mm	/12 1275 x 134mm	/15 1575 x 84mm	/15 1575 x 134mm
Driver	/STD Non Dimming	/DALI DALI Dimming	/1-10v 1-10v Dimming	/SDIM Switch Dimming	/WI Wireless Control	
Colour Temperature	/840 4000k					
Body Colour	Grey					
Diffuser Options	Opal Diffuser					
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency		
To Specify: MIVP-ECO LED, 27.6W, 3780lm, 1275mm, 84mm wide, 4000k, LED surface mounted finished grey supplied complete with standard control gear. Part code: MIVP-ECO/27.6W/3780lm/12/STD/840						

