

10000



The MIVP-GLD is a durable LED lights with aluminium die-cast housing. Designed for demanding environment such as gyms, warehouses, cold storage, factories and ect. Featuring secure hex-screw fastening and high-efficiency lighting.

- A range of lumen outputs from 3250lm - 8450lm
- Colour Temperatures: 4000k - 6500k
- Colour: Grey RAL7035 (/GR)
- Available with Dimming (/STD/1-10V/DALI/SDIM)
- Wireless Emergency (/ME3-WI) & Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Mountings: Surface Mounted or Suspended (/SM/WS)
- Diffuser: Polycarbonate
- IP Rating: IP66
- Sensor: Micro Sensor available (/MS)
- Distribution: 120 Degree
- Housing: Die cast aluminium
- Dimensions: (Length x Width x Depth)
 - /6 - 660 x 100 x 95mm
 - /12 - 1170 x 100 x 95mm

Product	MIVP GLADIATOR Linear LED Vapour Proof Luminaire				
Light Source	LED				
System Power Luminaire lumens (4000K)	/25W 3250lm	/35W 4550lm	/35W 4550lm	/50W 6500lm	/65W 8450lm
Lengths	/6 660mm		/12 1170mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/1-10v 1-10v Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/840 4000k			/865 6500k	
Mounting	/SM Surface Mounted			/WS Wire Suspended	
Distribution	120 Degree Symmetric Optic				
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency		/ME3-WI Three hour Wireless addressable emergency
To Specify: MIVP GLADIATOR LED, 35W, 1170mm length, 4550lm, 4000k, Wire Suspended, finished grey and supplied with standard control gear. Part code: MIVP-GLD/12/35W/4550m/STD/840/WS					

600mm Version



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3
Style
Range abbreviation
Wattage
Lumens
Size
Driver
Colour Temperature
Options
Emergency

How to Specify