



Low maintenance, affordable and efficient IP65 LED bulkhead luminaire.

Designed with integral sensor options.

- A range of lumen outputs from 1250lm or 1800lm
 - Colour Temperature: 4000k
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Available with microwave sensor for presence detection and presence detector for corridor function available (/MW/CDR)
 - Diffuser: Opal (/OP)
 - IP65 as standard
- Dimensions: Ø 340mm x 112mm (Dia X Depth)

Product	MIS/MOONDISC-IP65 Surface LED circular		
Lamp	LED		
Lamp Power	/15W 1250lm	/22W 1800lm	
Size Depth	Ø340mm 112mm		
Driver	/STD Non Dimming		
Colour Temperature	/840 4000k		
Colour	/WH White		
Diffuser Options	/OP Opal Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: MIS MOONDISC-IP65 LED, 15W, 4000k, 1250lm LED surface circular finished white supplied complete with standard control gear and opal diffuser. Part code: MIS/MOONDISC-IP65/15W/1250lm/STD/840/WH/OP			

