



**The PEGASUS is a highly efficient luminaire featuring a foldable design for beam angle adjustment, push-fit wiring, and a durable steel body with a prismatic polycarbonate cover. Suitable for warehouses, garages, and workshops.**

- A lumen outputs from 15000 - 22500lm
- Colour Temperatures: 4000K
- Beam Angles : Adjustable
- Colours: White (/WH)
- Available with Dimming (/STD/DALI)
- Available with Emergency (/ME3/ME3-ST/ME3- PRO)
- Supplied with BESA Brackets for Surface Mounting and hooks for Suspension
- Mountings: Surface Mounted or Suspended (/SM/WS)
- Diffuser: Prismatic Polycarbonate Diffuser
- IP Rating: IP20
- Sensor: Microwave Sensor or PIR Sensor (/MS/PIR)
- Dimensions Fully Expanded: (Length x Width x Height)  
600 x 246 x 89mm
- Dimensions When Folded : (Length x Width x Height)  
600 x 129 x 89mm

Product	MI/PEGASUS Industrial, Adjustable LED Luminaire		
Light Source	LED		
System Power Luminaire lumens (4000K)	/100W 15000lm	/130W 19500lm	/150W 22500lm
Dimensions	Fully Open - 600 x 246 x 89mm, Folded - 600 x 129 x 89mm		
Driver	/STD Non Dimming		
Colour Temperature	/840 4000K		
Colour	/WH White		
Beam Angle	Fully Adjustable		
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: PEGASUS adjustable LED luminaire, 100W delivering 15000lm (4000K), fully adjustable beam angle, Surface mounted installation, supplied with BESA brackets. Supplied with STD control gear and finished in White. Part Code: MI/PEGASUS/100W/15000lm/STD/840/WH/SM			

Luminaire When Folded



M	I	R	/S	W	/L	M	S	I	/D	I	/8	40	/O	P	T	/E	3
How to Specify	Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency								