



A circular suspended Direct/Indirect Phantom. The Phantom provides an elegant source of illumination through its unique optic.

- A lumen output of 6655lm
- Colour Temperatures: 3000k - 4000k - 6000k
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Integral control gear for the standard product.
- Distribution: Direct/Indirect
- Mountings: 3-point wire suspension as standard.
- Please note, dimming and emergency options require remote boxes.
- Dimensions: (Diameter x Depth)
Ø580 x 13mm

Product	MIS/PHAN-C Circular Suspended Direct /Indirect Luminaire			
Light Source	LED			
System Power <small>Luminaire lumens (4000K)</small>	/60W 6655lm			
Size	Ø580 x 13mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k	/840 4000k	/860 6000k	
Colour	/WH White		/BK Black	
Diffuser Options	/CL Clear Optic			
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency
To Specify: PHANTOM-C, 60W, 4000k, 6655lm LED suspended circular finished white supplied complete with standard control gear and clear diffuser. Part code: MIS/PHAN-C/60W/6655lm/STD/840/WH/CL				

